



**DATA SHEET FOR SUBMERSIBLE ELECTRIC
SEWAGE PUMPS**

Description	Value
General information:	
Product name:	submersible sewage pump
Site:	as required
Product Model:	WQ200-300-10-22
Technical:	
Rated flow:	300m ³ /h
Rated head:	10m
Main power supply:	380v, 50hz, 3phase
Type of impeller:	enclosed
Impeller stages:	1
Shaft seal:	mechanical seal
Cooling Type:	oil cooling
Cable:	4-5m

Main Materials:	
Pump casing:	Cast iron
Impeller:	Cast iron
Shaft:	45# steel(Better strength and toughness)
Motor:	Cast iron

Installation:	
Outlet diameter:	200mm
Max. through particles:	70mm
The lowest water level:	835mm
Inst dry/wet:	submerged
Installation:	vertical

Liquid:	
Pumped liquid:	Sewage water
Maximum liquid temperature:	40°C
Relative density:	1050kg/m ³
PH:	4-10
Kinematic viscosity:	3-6Pas

Company name:
Henan Bulletproof Electromechanical Equipment Co., Ltd.

Created by: Zoya
Phone: 86-13526854143
Date: 21/11/2019


Description	Value
Motor data:	
Number of poles:	4
Rated power :	22 kW
Mains frequency:	50 Hz
Rated voltage:	380V, 3phase
Rated speed:	1450rpm
Insulation class	H
IP class:	IP68
Voltage tolerance:	=5/-5%
Pump Efficiency:	68%
Working system:	S1
Lifting ring:	Yes
Themal protection:	Yes
Prober:	Yes



PERFORMANCE CURVE FOR SUBMERSIBLE ELECTRIC SEWAGE PUMPS

Company name:
Henan Bulletproof Electromechanical Equipment Co., Ltd.

Created by: Zoya
Phone: 86-13526854143
Date: 21/11/2019



				性能曲线图				
标记	头数	更改文件号	签字	日期	图样标记	重量	比例	泵类别
设计			标准化					
审核								WQ200-300-10-22
工艺			日期		共 页		第 页	