



DATA SHEET FOR SUBMERSIBLE PUMP

Created by: Zoya

Phone: 86-13526854143

Description	Value
General information:	
Product name:	Submersible pump
Site:	As required
Product Model:	QS50-15
Technical:	
Rated flow:	50m ³ /h
Rated head:	15m
Pump efficiency:	67%
Main power supply:	3phase, 380V, 50Hz
Type of impeller:	Enclosed
Impeller stage:	1
Main Materials:	
Pump casing:	SS304
Impeller:	SS304
Shaft:	45# steel
Installation:	
Pump outlet diameter:	3inch
Type of installation:	Vertical or horizontal
Inst dry/wet:	Wet
Liquid:	
Pumped liquid:	Clean water
Maximum liquid temperature:	20°C
PH:	6.5-8.5
Solid content in the water(as mass)	no more than 0.01%


Description	Value
Motor data:	
Voltage:	3phase, 380V
Frequency:	50 Hz
Rated power :	4 kW
Number of poles:	2
Rated speed:	2900rpm
Motor efficiency:	76.00%
Power factor	0.79
Insulation class	F
Level of production:	IP68
Working system:	S1
Motor cooling mode:	Water cooling



PERFORMANCE CURVE

Created by: Zoya

Phone: 86-13526854143



性能曲线图

泵类别

QS50-15

标记	处数	更改文件号	签字	日期
设计			标准化	
审核				
工艺			日期	

图样标记	重量	比例
共 页	第 页	

